



Ambient vibration based seismic evaluation of isolated Gülburnu highway bridge

Ahmet Can Altunişik*, Alemdar Bayraktar, Barış Sevim, Şevket Ateş

Karadeniz Technical University, Department of Civil Engineering, 61080 Trabzon, Turkey

ARTICLE INFO

Article history:

Received 23 December 2010

Received in revised form

30 May 2011

Accepted 31 May 2011

Available online 29 June 2011

Keywords:

Ambient vibration test

Finite element model updating

Highway bridge

Operational modal analysis

Seismic evaluation

Friction pendulum isolators

ABSTRACT

This paper describes ambient vibration based seismic evaluation procedure of an isolated highway bridge. The procedure includes finite element modeling, ambient vibration testing, finite element model updating and time history analysis. Gülburnu Highway Bridge located on the Giresun–Espiye state highway is selected as a case study. Three dimensional finite element model of the bridge is created by SAP2000 software to determine the dynamic characteristics analytically. Since input force is not measured, Operational Modal Analysis is applied to identify dynamic characteristics. Enhanced Frequency Domain Decomposition and Stochastic Subspace Identification methods are used to obtain experimental dynamic characteristics. Analytical and experimental dynamic characteristic are compared with each other and finite element model of the bridge is updated by changing of material properties to reduce the differences between the results. Analytical model of the bridge after model updating is analyzed using 1992 Erzincan earthquake record to determine the seismic behavior. EW, NS and UP components of the ground motion are applied to the bridge at the longitudinal, transverse and vertical directions, respectively. It is demonstrated that the ambient vibration measurements are enough to identify the most significant modes of highway bridges. Maximum differences between the natural frequencies are reduced averagely from 9% to 2% by model updating. It is seen from the earthquake analyses that friction pendulum isolators are very effective in reducing the displacements and internal forces.

© 2011 Elsevier Ltd. All rights reserved.

1. Introduction

Finite element analyses of important engineering structures such as highway bridges are performed in the design phase by experienced engineers to determine the structural behavior. However, material properties, boundary conditions and section properties accepted in the analyses can be changed by some reasons such as workers' mistakes while construction, different load cases to be exposed to the structure in the course of time which is not considered in the design, the difficulty in defining the exact material properties and the difficulty in matching the true connection behavior. So, performance of such bridge has to be controlled with the help of field testing or experimental measurements.

It is generally known that natural frequencies and mode shapes obtained from field testing do not coincide with those of the analytical model. The problem of how to modify the analytical model from the dynamic measurements is known as the model

updating in structural dynamics [1]. The main purpose of the model updating procedure is to minimize the differences between the analytically and experimentally determined dynamic characteristics by changing some uncertainty parameters such as material properties or boundary conditions.

In the literature, there are some studies related to finite element modeling and experimental measurements of highway bridges. Bayraktar et al. [2] determined the dynamic characteristics of Kömürhan Highway Bridge located on Elazığ–Malatya highway in Turkey using finite element analyses and ambient vibration tests. Whelan et al. [3] studied on real time wireless vibration monitoring of a bridge with single span integral abutment using operational modal analysis in service condition. Liu et al. [4] investigated finite element analyses, field measurements using ambient vibration tests and seismic evaluation of a three-span highway bridge subjected to a virtual ground motion. Kwasniewski et al. [5] presented an experimental study for a preselected typical highway bridge. Static and dynamic field tests were performed on a two-lane concrete highway bridge. During the tests, one or two fully loaded trucks crossed over the bridge, which was instrumented with strain gauges, accelerometers, and displacement transducers. Feng et al. [6] applied a neural network based system identification technique to a highway bridge using

* Corresponding author. Tel.: +90 462 377 40 20; fax: +90 462 377 26 06.

E-mail addresses: ahmetcan8284@hotmail.com (A.C. Altunişik), alemdar@ktu.edu.tr (A. Bayraktar), bsevim18@hotmail.com (B. Sevim), sates@ktu.edu.tr (Ş. Ateş).